American Cabling

CH-60615GS CH-60815GS






GLASS RACK

15U Width 60cm.

Scope of Application

The premium innovation design, an elegant appearance, delivered with best enterprise service, support and reliability. LINK Glass Rack offered high strength product, high durability and efficiency at work, also can support to install 19"Standard's equipment.

Drawing









*For reference only

Technical Standard

- ANSI/EIA-310D
- IEC 60297-1
- IEC 60297-2
- BS 5954 Part : 2
- DIN 41494
- 19"Rack Standard
- ISO 9001 :2015
- ISO 14001 : 2015















Features

- Modular knock down platform designed with grounding system for convenient assembly and adding accessories.
- Front door with "See-through" 5.0mm tempered glass and perforated surrounding for better ventilation.
- Provided swing handle lock at front and rear door.
- Side panels easy removable by slide lock and security lock for installation and maintenance.
- Raised roof with vented can be mounted the fan sets and provided the space for cable access at the front and back of the roof with cover.
- Base with the slide shutter and the space for cable access and provided cover to close both of front and back when
- 10x10mm Mounting pole made from Galvanized Steel with Zinc coated and can be adjustable with screened Rack unit (U) on the pole.
- Up and down movable stand with 360°° caster made from Nylon 6 for convenience to move.
- The cable can be access from the top and the base.

Material

: 2.0 mm Electro-galvanized steel sheet Frame Front Door : 1.2 mm Electro-galvanized steel sheet

: 5.0 mm Tempered glass

: 1.2 mm Electro-galvanized steel sheet Rear and Side Panels Side Panel : 1.2 mm Electro-galvanized steel sheet

Mounting Pole : 2.0 mm Electro-galvanized steel sheet with Zinc coated

Electrostatic powder coating, Black (RAL9004)

Order Information

Part number	Description	U Height (U=4.45 cm.)	Width (cm.)	Depth (cm.)	Height (cm.)
CH-60615GS	19"LINK GLASS RACK 15U, (60 x 60 cm.)	15U	60	60	88
CH-60815GS	19"LINK GLASS RACK 15U, (60 x 80 cm.)	15U	60	80	88

