





UF-2022A  
UF-2024A

## F.O. DISTRIBUTION UNIT (Snap-In), WALL MOUNT

### Scope of Application


LINK Fiber Optic Distribution Unit (FDU) design with innovation technology very easily install and very flexible to use by wall mount type with security lock. Supply with fiber splicing tray, cable gland, key, screw, nylon anchor and label comply with standard ANSI/TIA-568.3-D & ISO/IEC11801 lasted edition.

### Drawing



UF-2022A

2 SNAP- IN WALL MOUNT TYPE



UF-2024A

4 SNAP- IN WALL MOUNT TYPE



### FEATURES AND BENEFITS

- Designed for all fiber optic wiring.
- Suitable for installation on wall.
- Structures made from Electro galvanize sheet steel, very durability.
- Top and Bottom cable entry integral grommets for preventing dust from entering the system.
- Uses with all type of LINK fiber optic adapter snap plate such as ST, FC, SC and LC.
- Included Fusion Splicing Tray for manage and retain fusion splice protector sleeve.
- Fusion Splicing Tray made from PC/ABS to control bending radius subject to the standard.
- Fusion Splicing Tray support 24 fiber cores, can stacking & hinged.
- Dual doors with separate locking options for quick to install or manage and security.
- The laser symbol and LINK trademark are Cleary screened at the front.
- Lockable front door provides added security and prevent unwanted access.
- UF-2022A support 6-24 fiber ports, UF-2024A support 6-48 fiber ports.
- For 6 LC Quad (24F) adapter snap plate, UF-2022A up to 48 fiber ports, UF-2024A up to 96 fiber ports.
- Accessories provided in bagged.
  - 2 cable glands for UF-2022A, 4 cable glands for UF-2024A
  - 2 keys
  - 4 sets of screw and nylon anchor
  - 4 cable ties for UF-2022A, 8 cable ties for 2024A
  - 1 label



## SPECIFICATION

	UF-2022A	UF-2024A
<b>Panel</b>		
Material	Electro Galvanize Steel	Electro Galvanize Steel
Thickness	1.2 mm.	1.2 mm.
<b>Front Door</b>		
Material	Electro Galvanize Steel	Electro Galvanize Steel
Thickness	1.5 mm.	1.5 mm.
<b>Wire Saddle Tie Mount</b>		
Material	Electro Galvanize Steel	Electro Galvanize Steel
Thickness	1.0 mm.	1.0 mm.
<b>24F Fusion Splicing Tray</b>		
Material	PC/ABS, 1 set	PC/ABS, 2 set
<b>Label</b>		
Material	Paper, White Color	Paper, White Color
<b>Slide Latch</b>		
Material	ABS, Grey Color	ABS, Grey Color
<b>Grommet</b>		
Material	PVC, Black Color	PVC, Black Color
<b>Edging</b>		
Material	Nylon 66, Natural Color	Nylon 66, Natural Color
<b>Dimension</b>		
W x D x H (cm.)	33.0 x 9.2 x 21.4	33.1 x 9.2 x 31.6

## ORDER INFORMATION

Part Number	Description	No. of Fusion Splicing Tray	No. of Adapter Plate	Color
UF-2022A	2 SNAP- IN WALL MOUNT TYPE	1	2	Light Grey
UF-2024A	4 SNAP- IN WALL MOUNT TYPE	2	4	Light Grey

\*Available white and other color on request

Specifications subject to change without notice.

© 2025 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

UF-2022A, UF-2024A-V1.3\_\_200325