



- UF-3022A
- UF-3024A
- UF-3027A
- UF-3029A
- UF-3061A
- UF-3062A


LINK AMERICAN STANDARD



UF-30XXA in full view



UF-30XXA cutaway view




sealing fitting

### Scope of Application

LINK FOSC (Fiber Optic Splice Closure) dome Type, which supports optical cable link, branch, distribution and storage. It can be used for both single core cable and ribbon cable. The unique mechanical sealing method owns national patent and perfect sealing. It's suitable for wall-mounting, aerial, pole-mounting and direct buried applications.

### Drawing



### FEATURES AND BENEFITS

- Available in 4 ports for single cable
- Splice trays are hinged for direct access to any splice without disturbing other trays.
- Can be used in wall-mounting, aerial, underground, hand hole-mounting and duct-mounting
- Design branch closure or inline closure with mechanical sealing method : No heat shrink
- Mechanical sealing adjusts to cable size
- Reliable and easy to install with clamping system
- High compressive strength, no require special tool
- Fiber optic splice trays (FOSTs) are designed in SLIDE-IN-LOCK and its opening angle is about 90°
- Easy and fast to increase and reduce FOSTs
- Protection Level: IP68
- Included accessories



## SPECIFICATION

<b>Dimension</b>	415 × Ø 190 mm
<b>Weight</b>	2.5 to 3.1 kg
<b>Numbers of cable port</b>	4 ports for single cable
<b>Diameter of suitable cable</b>	Ø range 8 to 16 mm
<b>Maximum numbers of trays</b>	6(12F), 4(24F)
<b>Maximum capacity (single core)</b>	96 cores
<b>Sealing method</b>	mechanical
<b>Capacity of one tray</b>	12 and 24 cores
<b>Insulation resistance</b>	≥2×10 <sup>4</sup> MΩ
<b>Voltage resistance strength</b>	15KVDC/1mi, no puncture, arc-over
<b>Environmental temperature</b>	-40°C to +65 °C

## ORDER INFORMATION

Part Number	Description	No. of Cable	Dimension
		Ports	(mm)
UF-3022A	24 Cores FOSC, Dome Type with 2 Tray (12F)	4	415 ×Ø 190
UF-3023A	48 Cores FOSC, Dome Type with 4 Tray (12F)	4	415 ×Ø 190
UF-3027A	72 Cores FOSC, Dome Type with 6 Tray (12F)	4	415 ×Ø 190
UF-3029A	96 Cores FOSC, Dome Type with 4 Tray (24F)	4	415 ×Ø 190
UF-3061A	Splice Tray (Plastic) 12 Fibers for Dome Closure	-	Spare Part
UF-3062A	Splice Tray (Plastic) 24 Fibers for Dome Closure	-	Spare Part

Specifications subject to change without notice.

© 2023 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

UF-302XA-V1.0\_151223