




UF-3022A
UF-3024A
UF-3027A
UF-3029A
UF-3061A
UF-3062A



UF-30XXA in full view



UF-30XXA cutaway view




sealing fitting

Scope of Application

LINK FOSC (Fiber Optic Splice Closure) dome Type, which supports optical cable link, branch, distribution and storage. It can be used for both single core cable and ribbon cable. The unique mechanical sealing method owns national patent and perfect sealing. It's suitable for wall-mounting, aerial, pole-mounting and direct buried applications.

Drawing



FEATURES AND BENEFITS

- Available in 4 ports for single cable
- Splice trays are hinged for direct access to any splice without disturbing other trays.
- Can be used in wall-mounting, aerial, underground, hand hole-mounting and duct-mounting
- Design branch closure or inline closure with mechanical sealing method : No heat shrink
- Mechanical sealing adjusts to cable size
- Reliable and easy to install with clamping system
- High compressive strength, no require special tool
- Fiber optic splice trays (FOSTs) are designed in SLIDE-IN-LOCK and its opening angle is about 90°
- Easy and fast to increase and reduce FOSTs
- Protection Level: IP68
- Included accessories



SPECIFICATION

Dimension	415 × Ø 190 mm
Weight	2.5 to 3.1 kg
Numbers of cable port	4 ports for single cable
Diameter of suitable cable	Ø range 8 to 16 mm
Maximum numbers of trays	6(12F), 4(24F)
Maximum capacity (single core)	96 cores
Sealing method	mechanical
Capacity of one tray	12 and 24 cores
Insulation resistance	≥2×10 ⁴ MΩ
Voltage resistance strength	15KVDC/1mi, no puncture, arc-over
Environmental temperature	-40°C to +65 °C

ORDER INFORMATION

Part Number	Description	No. of Cable	Dimension
		Ports	(mm)
UF-3022A	24 Cores FOSC, Dome Type with 2 Tray (12F)	4	415 ×Ø 190
UF-3024A	48 Cores FOSC, Dome Type with 4 Tray (12F)	4	415 ×Ø 190
UF-3027A	72 Cores FOSC, Dome Type with 6 Tray (12F)	4	415 ×Ø 190
UF-3029A	96 Cores FOSC, Dome Type with 4 Tray (24F)	4	415 ×Ø 190
UF-3061A	Splice Tray (Plastic) 12 Fibers for Dome Closure	-	Spare Part
UF-3062A	Splice Tray (Plastic) 24 Fibers for Dome Closure	-	Spare Part

Specifications subject to change without notice.

© 2025 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

UF-302XA-V1.4__170625