




- UF-3042A
- UF-3044A
- UF-3047A
- UF-3049A
- UF-3063A
- UF-3064A


LINK AMERICAN STANDARD



UF-304XA in full view



UF-304XA cutaway




sealing fitting

### Scope of Application

LINK FOSC (Fiber Optic Splice Closure), horizontal type, which supports optical cable link, branch, distribution and storage. It can be used for both single core cable and ribbon cable. The unique mechanical sealing method owns national patent and perfect sealing. It's suitable for wall-mounting, aerial, pole-mounting and direct buried applications.

### Drawing



### FEATURES AND BENEFITS

- Available in 6 ports for entrance cable.
- Splice trays are hinged for direct access to any splice without disturbing other trays.
- Can be used in wall-mounting, aerial, underground, hand hole-mounting and duct-mounting with IP68 protection rating.
- Design branch closure or inline closure with mechanical sealing method: No heat shrinks.
- Mechanical sealing adjusts to cable size.
- Reliable and easy to install.
- High compressive strength, no require special tool.
- Fiber optic splice trays (FOSTs) are designed in SLIDE-IN-LOCK and its opening angle is about 90°.
- Easy and fast to increase and reduce FOSTs.
- Included splice protective sleeve and accessories.



## SPECIFICATION

Dimension	396 × 190 x 126 mm
Weight	2.5 to 2.82 kg
Numbers of cable port	6
Diameter of suitable cable	Ø range 8 to 13 mm ; 2 port 8 to 16 mm ; 2 port 8 to 20 mm ; 2 port
Maximum numbers of trays	6(12F), 4(24F)
Maximum capacity (single core) cores	96
Sealing method	mechanical
Capacity of one tray	12 and 24 cores
Insulation resistance	≥2×104MΩ
Voltage resistance strength	15KVDC/1min, no puncture, arc-over
Environmental temperature	-40°C to +65 °C

## ORDER INFORMATION

Part Number	Description	No. of Cable Ports	Dimension (L x W x Hmm)
UF-3042A	24 Cores FOOSC, Horizontal Type with 2 Tray (12F)	6	396 × 190 x 126
UF-3044A	48 Cores FOOSC, Horizontal Type with 4 Tray (12F)	6	396 × 190 x 126
UF-3047A	72 Cores FOOSC, Horizontal Type with 6 Tray (12F)	6	396 × 190 x 126
UF-3049A	96 Cores FOOSC, Horizontal Type with 4 Tray (24F)	6	396 × 190 x 126
UF-3063A	Splice Tray (Plastic) 12 Fibers for Horizontal Closure	-	Spare Part
UF-3064A	Splice Tray (Plastic) 24 Fibers for Horizontal Closure	-	Spare Part

Specifications subject to change without notice.

© 2023 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

UF-304XA-V1.0\_\_151223