

# FIBER OPTIC OUTDOOR TERMINAL STEEL CABINET




- UF-4112A
- UF-4114A
- UF-4116A
- UF-4119A
- UF-4120A
- UF-4114A

LINK AMERICAN CABLING

## Scope of Application

LINK Fiber Optic Terminal, Outdoor Steel offers ideal environment for optical fibers to be spliced and working under both indoor and outdoor environments. It is perfect cost-effective solution provider in the optical fiber network.

## Drawing



## FEATURES

- Supported cable termination, splicing and distribution.
- Material: Body - Aluminum light weight, thickness 2 mm.
- Inner Plate - Cold-rolled Steel, thickness 1.5 mm.
- I Frame - Aluminum light weight, thickness 2 mm.
- Easy to install: It is ready for wall mount and pole mount installation kits provided.
- Solid and fully-closed structure with pleasing appearance.
- Cable fixing units provided to fix the outdoor optical cable.
- The bottom of the cabinet has a hole for the cables in - out.
- Accommodates both cable glands as well as tie-wraps.
- Provided 6 mm<sup>2</sup> grounding wire is connected between the body and front door.
- Mounting of Snap-In Plate can slide in and out to easy installation.
- Suitable for all of LINK adapter snap plate such as ST, SC, FC and LC Adapter Snap Plate.
- Design individual removable each splice tray
- Support IP65 standard.
- Supported security locking system.
- Color coating reaching 100 microns (µm)
- The laser symbol and LINK trademark are clearly screened at the front.



## SPECIFICATIONS

Part Number	Capacity	No. of Splice Tray	Capacity Snap –In Plate	No. of In/Out Cable port $\Phi$ 28.5mm (PG21)	Dimension (mm) H x W x D
UF-4112A	24 Cores	1	2	2	403.5X350X180
UF-4114A	48 Cores	2	4	2	403.5X350X180
UF-4116A	72 Cores	3	6	8	460X390X200
UF-4119A	96 Cores	4	8	8	550X490X250
UF-4120A	120 Cores	5	10	12	550X490X275
UF-4144A	144 Cores	6	12	12	550X490X300

## SPECIFICATIONS

Temperature	-40°C to 70°C
-------------	---------------

## ACCESSORIES

- Cable tie
- Cable gland
- Protective sleeves
- Labeling paper
- Heavy Duty Master Key
- Screw and Nut
- Splice Tray
- I-Frame For Wall Mount

## ORDER INFORMATION

Part Number	Descriptions	Capacity	Color
UF-4082A	FDU SLIDE 12-24 C, Slide w/Cover, Rack Mount, w/Tray & Acc.	24F	Light Gray
UF-4084A	FDU SLIDE 24-48 C, Slide w/Cover, Rack Mount, w/Tray & Acc.	48F	Light Gray
UF-4086A	FDU SLIDE 48-72 C, Slide w/Cover, Rack Mount, w/Tray & Acc.	72F	Light Gray
UF-4089A	FDU SLIDE 72-96 C, Slide w/Cover, Rack Mount, w/Tray & Acc.	96F	Light Gray
UF-4102A	FDU SLIDE 120-144 C, Slide w/Cover, Rack Mount, w/Tray & Acc.	144F	Light Gray

\*Note : All model without pigtail and adapter

Specifications subject to change without notice.

© 2025 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

UF-41XXA-V1.2\_\_210325