



CH-12412



16A


PDU C13 OUTLET

12 C13 OUTLET (Circuit Breaker 16A + Power Plug 16A)

Scope of Application

LINK Power Distribution Unit (PDU) can meet the general requirements of power distribution and special demand. Solid, easy installation and modular composite structure are the basic characteristics. Security and stability are our guarantee for the products. The products can meet the installation requirements of 19" standard cabinet and non-standard cabinet. More control, outlet standards, accessibility functions can be customized. Applications support datacenter, telecommunications, PC systems, audio video, security, sound and other. Ideal for distribution of UPS, generator or other AC power to protected equipment.

Drawing



Technical Standard

- IEC 60309
- RoHS



Specifications

- Nominal Voltage : 220 - 250VAC
- Frequency : 50/60Hz
- Maximum Amps : 16A
- Maximum Power : 3,680W
- Plug Type : IEC 60309 2P+E (16A)
- Outlet Type : IEC 60320 C13
- Circuit Breaker : 16A (1Pole)
- Power Cord Length (m) : 3m.
- Power Cord Electrical Wiring : 3x2.5mm² (16A)
- Socket material : Engineering Plastic
- Panel Material : Aluminium Alloy
- Outlet quantity : 12 Outlets
- PDU Bracket Kit : Included 1 Pairs
- Warranty : 1 Year

Order Information

Part number	Description	Power Cord
CH-12412	PDU 12 C13 Outlet (Circuit Breaker 16A + Power Plug 16A)	3m.

Specifications subject to change without notice.

© 2023 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

CH-12412-V1.3-190325