

# CCTV OUTDOOR CABINET

TWO LAYER DOOR, IP55




UV-9012H-IP55

## Scope of Application

Hanging cabinet type for outdoor installation, suitable for CCTV system, Suitable for Fiber Optic Equipment, Industrial Media Converter and Industrial Ethernet Switches

## Drawing



## Technical Standard

- ASTM D522
- ASTM D3363
- ASTM D3359
- Salt spray test 500 hrs.
- ISO 9001 : 2015
- ISO 14001 : 2015



## Features

- Hanging cabinet type for outdoor, suitable for CCTV system and fiber optic distribution.
- Two Layers Door suitable for harsh environment with outdoor installation. Designed of two layers with the Sun Shield layer for better protection.
- Produced from Electro-Galvanized sheet steel with thickness of 1.2mm, Light weight and completed rust proof.
- Medium gray color, coated and baked using the Electro-static Powder Coating system in accordance with the international ASTM standards.
- It has a water and dust protection rating of IP55.
- Provide build in push handle lock is made from stainless steel, offering high strength and excellent rust resistance at front door.
- Both sides of the cabinet are equipped with louvered ventilation openings designed to prevent water ingress. Inside the cabinet, dust filters are installed to protect against fine dust particles.
- Supporting by double steel bar with thickness of 2.0mm at Back side.
- Roof can accommodate two 4-inch ventilation fans (CK-80104) and features elongated capsule-shaped ventilation slots along the front side. An internal insect screen is included to prevent intrusion. This design effectively dissipates heat within the cabinet and helps extend the lifespan of the internal equipment
- Door and roof are equipped with a special black rubber material that provides high resistance to water and moisture, utilizing CNC Foam Gasket Technology to prevent water from entering the cabinet.
- Hinge is made from aluminum material, which is rust-resistant and corrosion-resistant.
- There is a supporting the UPS at the bottom of the cabinet can support the UPS or power supply.
- Provide 4 knock out holes with size 3/4" and 1" for cable entry and 2 mounting holes for Pilot Lamp
- Provide cable guide inside the cabinet for manages all the cables.
- Provide removable component plate with thickness 1.5mm. Plate can remove out from the cabinet for Din Rail to install the equipment.
- Plate is pre-drilled for M4 rivet nuts, accommodating at least two layers of splice trays. It supports the installation of 2 adapter snap plates (up to 48 cores).
- Provide ground wire connecting between structure cabinet and front door.

## Material

- Frame : 1.2 mm Electro-galvanized steel sheet
- Removable Plate : 1.5 mm Electro-galvanized steel sheet
- Back Support Bar : 2.0 mm Electro-galvanized steel sheet
- Electrostatic powder coating, Medium Gray

## Order Information

Part number	Description	Height (cm.)	Width (cm.)	Depth (cm.)	IP Rating
UV-9012H-IP55	CCTV OUTDOOR STEEL CABINET, Two LAYER Door	68	46.8	26.8	IP55

## Recommend Accessories

Part number	Description
UF-2082	Spare Splice Tray 24F (Plastic)
CK-80104	FAN 1xØ4" HEAVY DUTY FAN
CH-10304A	PDU 4 TIS OUTLET (Lighting SW w/Guard + Protection 16A)

Specifications subject to change without notice.

© 2023 LINK CORP. ALL RIGHTS RESERVED

www.linkcable.com

UV-9012H-IP55-V2.1-250326